



## TECHNICAL BULLETIN

# Eco-Float Aid 348

### PRODUCT DESCRIPTION:

Eco-Float Aid 348 is an environmentally friendly, patent pending flotation agent for use in conjunction with fatty acids in the primary float process.

### APPLICATIONS:

Eco-Float Aid 348 is typically added at a rate of 0.5 to 1.0 pounds per ton.

### TYPICAL PROPERTIES:

Appearance:	Dark brown liquid
Density @ 100°F:	7.1 – 7.5 ppg
Viscosity @ 100°F:	<100 cps
Flash Point:	>200°F (Nonflammable)

### STORAGE AND HANDLING:

This product will titer, please store above 20°F. If titered the product should be warmed and mixed prior to use.

### REGULATORY STATUS:

Eco-Float Aid is readily biodegradable.

Eco-Float Aid 348 does not contain:

- Heavy Metals
- Dioxins
- Poly Nuclear Aromatics
- Carcinogens
- PCBs
- Chlorides

Eco-Float Aid 348 is TSE/BSE free and does not contain prohibited materials defined in 21 CFR 589.2000.

The components of Eco-Float Aid 348 are listed on the TSCA inventory.

This product does not contain components that are regulated by California Proposition 65.

**PACKAGING INFORMATION:**

Eco-Float Aid 348 is available in bulk, tote bins at 2200 pounds net, and 55 drums with a net weight of 400 pounds.